

Enduro Engineering Skid Plate Installation



Note: We recommend using a thread locking agent on all 4 skid plate mounting bolts.

1 Using a small screwdriver pry out the 2 plastic plugs from the threaded holes in the rear of the frame. Be careful not to pry too hard on the side of the hole and damage the threads.

2 Insert the front skid plate mounting bracket between the front motor mount brackets on the frame as shown in **(Figure 2)**.

3 Insert the two supplied 6x16mm button head bolts through the small holes in each side of the frame above the front motor mount bolt **(Figure 3)** and through the holes in the skid plate mounting bracket. Now place one of the supplied flat washers and start one of the supplied self locking nuts on each bolt. Using a 4mm Allen wrench and a 10mm box end wrench to hold the locking nut, tighten the bolts just enough to allow slight rotation of the mounting bracket.

4 Hold the skid plate up to the bike and insert the 2 supplied 6x20mm button head bolts thru the rear skid plate mounting holes and into the threaded holes in the rear of the frame. **(Figure 4)** Do not tighten yet.

5 Insert 2 of the supplied 6x16mm button head bolts through the front skid plate mounting holes and into the threaded holes in the front mounting bar as shown in **(Figure 5)**. It may be necessary to slightly rotate the mounting bracket to align mounting holes. Do not tighten yet.

6 Make sure the skid plate is centered and not in contact with the ignition cover on the left side of the engine.

7 Tighten down the front mounting bar to frame bolts using a 4mm Allen wrench and a 10mm box end wrench to hold the locking nuts. **(Figure 6)**

8 Using a 4mm Allen wrench, tighten the 2 front and the 2 rear skid plate mounting bolts.




FIG 1



FIG 2



FIG 3



FIG 4



FIG 5



FIG 6

WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Enduro Engineering, Inc. (EEI) are to be installed by a licensed motorcycle dealer or a licensed motorcycle technician. Motorcycles can be dangerous. Serious injury, death and property damage can result from the use of motorcycles. This risk is increased by improper installation or misuse of after market parts. EEI's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by EEI, the responsibility of EEI is limited to either a refund of the purchase price or the replacement of the part if EEI determines the part to be defective, and subject to EEI's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to EEI products will void this limited warranty). EEI, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever. By purchasing an EEI product or a product sold by EEI, you (1) acknowledge the above disclaimer and agree to its terms; (2) agree that any claim brought against EEI arising from and/or pertaining to or otherwise related to a part manufactured, designed or sold by EEI must be brought in the Michigan State Courts located in the County of Ingham or in the Federal District Court for the Western District of Michigan and that Michigan law shall apply on all issues; and (3) any claim against EEI must be brought within one (1) year of purchase of the product. EEI makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose. R.JRF.Sec.randt.warninganddisclaimer.5 2 08

Enduro Engineering

QUALITY OFF-ROAD MOTORCYCLE PRODUCTS

INSTRUCTIONS

Skid Plate Installation

Part# 24-066